

Power cable - PLD E 608-CA-MS/0,6/FS/UL - 2702307

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 3-position, PVC, gray RAL 7001, Plug straight, black, on Socket straight, black, Cable length: 0.6 m

Product Description

The cable serves to connect multiple 600 class PLD enclosure lights in series.

RoHS

Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	80.000 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

Dimensions

Length of cable	0.6 m
-----------------	-------

Ambient conditions

Degree of protection	IP20
	IP40 (plugged in)

General

Rated current at 40°C	16 A
Rated voltage	250 V AC
Number of positions	3
Coding	black

Material

Material, knurls	not available
------------------	---------------

Power cable - PLD E 608-CA-MS/0,6/FS/UL - 2702307

Classifications

eCl@ss

eCl@ss 5.1	27049090
eCl@ss 8.0	27379201
eCl@ss 9.0	27141137

ETIM

ETIM 5.0	EC002498
----------	----------

Approvals

Approvals

Approvals


UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approval details

UL Recognized  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 118976

cUL Recognized  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm> FILE E 118976

cULus Recognized  <http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

Accessories

Accessories

Power distributor

Power cable - PLD E 608-CA-MS/0,6/FS/UL - 2702307

Accessories

T distributor - PLD E 608-CO-MS/FS/FR - 2702310



T-distributor with 2 sockets and one connector for series connection, black, 3-pos.
